



Références	Ø d mm	Ø D mm	B mm	C mm	T mm	Charges kN		Vitesse max. tr / min		Poids
						Dyn C	Stat Co	Graisse	Huile	g
30302	15	42	13	11	14.25	21.5	19.8	9 000	13 000	90
30203		40	12	11	13.25	18.3	19	9 000	13 000	74
30303	17	47	14	12	15.25	26	24.5	8 500	12 000	130
32303		47	19	16	20.25	34	35.5	8 000	11 000	170
32004		42	15	12	15	26	28.5	8 500	12 000	97
30204	20	47	14	12	15.25	25.8	26.4	8 000	11 000	120
30304		52	15	13	16.25	32	32	8 000	11 000	170
32304		52	21	18	22.25	42.4	47	7 500	10 000	221
32005		47	15	11.5	15	26	33.5	8 000	11 000	113
30205	25	52	15	13	16.25	30.1	32.9	7 500	10 000	150
32205		52	18	15	19.25	31	37	7 500	10 000	182
30305		62	17	15	18.25	43	43	6 700	9 000	250
31305		62	17	13	18.25	39	41	5 600	7 500	255
32305		62	24	20	25.25	58.3	60.3	6 000	8 000	360
32006		55	17	13	17	34	45.5	6 700	9 000	170
30206	30	62	16	14	17.25	40.5	45.1	6 300	8500	220
32206		62	20	17	21.25	49	61	6 300	8 500	280
30306		72	19	16	20.75	52.9	51.8	5 600	7 500	380
31306		72	19	14	20.75	46.5	49.5	5 000	6 700	390
32306		72	27	23	28.75	75.8	82.7	5300	7 000	550
32007		62	18	14	18	35.9	52.4	6 000	8 000	220
30207	35	72	17	15	18.25	50.5	54.7	5 300	7 000	320
32207		72	23	19	24.25	66.2	77.5	5 300	7 000	420
30307		80	21	18	22.75	71.2	72.5	5 000	6 700	520
31307		80	21	15	22.75	58.1	64	4 500	6 000	520
32307		80	31	25	32.75	95.3	106	4 800	6 300	730
32008		68	19	14.5	19	48.8	65.8	5 300	7 000	270
30208	40	80	18	16	19.75	57.9	62.4	4 800	6 300	420
32208		80	23	19	24.75	66.2	79.5	4 800	6 300	510
30308		90	23	20	25.25	83.9	91.3	4 500	6 000	700
31308		90	23	17	25.25	74.6	60.8	4 000	5 300	685
32308		90	33	27	35.25	105	122	4 000	5 300	993