


Roulement à rouleaux coniques



| Références | Dimensions mm | | | | | Vitesse max | | Charges kN | | Poids |
|------------|---------------|----|----|----|-------|-----------------|---------------|------------|------------|-------|
| | d Ø axe | D | B | C | T | Graisse t/mn | Huile t/mn | Dyn c | Stat co | g |
| S 30202 A | 15 | 35 | 11 | 10 | 11.75 | 9 400 | 13 500 | 11.76 | 11.28 | 56 |
| S 30203 | 17 | 40 | 12 | 11 | 13.25 | 8 500 | 12 000 | 14.64 | 15.84 | 74 |
| S 30204 | 20 | 47 | 14 | 12 | 15.25 | 8 000 | 11 000 | 20.64 | 21.12 | 120 |
| S 30205 | 25 | 52 | 15 | 13 | 16.25 | 7 500 | 10 000 | 24.08 | 26.32 | 150 |
| S 30206 | 30 | 62 | 16 | 14 | 17.25 | 6 300 | 8 500 | 32.40 | 36.08 | 232 |

| Références | Dimensions mm | | | | | Vitesse max | | Charges kN | | Poids |
|------------|---------------|-----|-----|------|------|-----------------|---------------|------------|------------|-------|
| | d Ø axe | D | T | d1 | D1 | Graisse t/mn | Huile t/mn | Dyn c | Stat co | g |
| SS F3-8 M | 3 | 8 | 3.5 | 3.2 | 7.8 | 19 000 | 28 000 | 0.92 | 0.59 | 0.9 |
| SS F4-10 M | 4 | 10 | 4 | 4.2 | 9.8 | 16 000 | 27 000 | 0.93 | 0.66 | 1.5 |
| SS F5-12 M | 5 | 12 | 4 | 5.2 | 11.8 | 14 000 | 22 000 | 1.06 | 0.94 | 2.1 |
| SS F6-14 M | 6 | 14 | 5 | 6.25 | 14 | 12 000 | 18 000 | 2.2 | 1.70 | 3.5 |
| SS F7-17 M | 7 | 17 | 6 | 7.2 | 17 | 10 000 | 15 000 | 3.9 | 2.68 | 6.5 |
| SS F8-19 M | 8 | 19 | 7 | 8.2 | 19 | 9 000 | 13 000 | 3.4 | 3.54 | 9.1 |
| SS F9-20 M | 9 | 20 | 7 | 9.2 | 20 | 8 000 | 13 000 | 3.9 | 3.57 | 9.9 |
| S 51100 | 10 | 24 | 9 | 10.5 | 24 | 6 700 | 10 000 | 8,59 | 7,65 | 20 |
| S 51200 | 11 | 26 | 11 | 11.5 | 26 | 6 000 | 9 000 | 10,88 | 8,84 | 30 |
| S 51101 | 12 | 26 | 9 | 12.5 | 26 | 6 700 | 10 000 | 8,84 | 8,93 | 22 |
| S 51201 | 13 | 28 | 11 | 13.5 | 28 | 5 600 | 8 500 | 11,31 | 10,46 | 34 |
| S 51102 | 14 | 28 | 9 | 15.5 | 28 | 6 300 | 9 500 | 9,01 | 10,20 | 24 |
| S 51202 | 15 | 32 | 12 | 16.5 | 32 | 5 000 | 7 500 | 14,20 | 13,86 | 46 |
| S 51103 | 16 | 30 | 9 | 17.5 | 30 | 6 300 | 9 500 | 9,69 | 12,33 | 28 |
| S 51203 | 17 | 35 | 12 | 18.5 | 35 | 5 000 | 7 500 | 14,71 | 15,98 | 53 |
| S 51104 | 18 | 35 | 10 | 20.5 | 35 | 5 300 | 8 000 | 12,84 | 16,75 | 40 |
| S 51204 | 19 | 40 | 14 | 21.5 | 40 | 4 000 | 6 000 | 19,13 | 22,53 | 82 |
| S 51105 | 20 | 42 | 11 | 25.5 | 42 | 4 500 | 6 700 | 16,75 | 23,97 | 59 |
| S 51205 | 21 | 47 | 15 | 36.5 | 47 | 3 800 | 5 600 | 23,80 | 30,60 | 120 |
| S 51106 | 22 | 47 | 11 | 31 | 47 | 4 300 | 6 500 | 17,51 | 28,05 | 68 |
| S 51206 | 23 | 52 | 16 | 31 | 52 | 3 400 | 5 300 | 25,08 | 37,40 | 150 |
| S 51107 | 24 | 52 | 12 | 36 | 52 | 4 000 | 5 300 | 18,79 | 34,43 | 90 |
| S 51108 | 25 | 60 | 13 | 41 | 60 | 3 600 | 4800 | 23,04 | 43,35 | 120 |
| S 51109 | 26 | 65 | 14 | 46 | 65 | 3 400 | 4 500 | 23,89 | 48,88 | 150 |
| S 51110 | 27 | 70 | 14 | 51 | 70 | 3 200 | 4 300 | 24,65 | 53,98 | 160 |
| S 51111 | 28 | 78 | 16 | 53 | 78 | 2 800 | 3 800 | 29,75 | 66,73 | 240 |
| S 51112 | 29 | 85 | 17 | 61 | 85 | 2 600 | 3 600 | 35,70 | 80,75 | 290 |
| S 51113 | 30 | 90 | 18 | 66 | 90 | 2 400 | 3 400 | 35,70 | 85,00 | 340 |
| S 51114 | 31 | 95 | 18 | 71 | 95 | 2 400 | 3 400 | 36,98 | 92,65 | 360 |
| S 51115 | 32 | 100 | 19 | 77 | 100 | 2 200 | 3 300 | 36,98 | 96,90 | 430 |
| S 51116 | 33 | 105 | 19 | 82 | 105 | 2 200 | 3 200 | 38,25 | 104,55 | 450 |
| S 51117 | 34 | 110 | 19 | 87 | 110 | 2 200 | 3 100 | 39,53 | 113,05 | 480 |

Butée à billes simple effet

