



Série SAPF 200

Série SBPF 200

Références	Dimensions mm									Vis	Roult.	Poids kg
	d	a	e	M	t	s	n	B1	K			
SAPF 201	12	81	63.5	7	2	7.1	6	28.6	28.6	M6	SA 201	0.30
SAPF 202	15	81	63.5	7	2	7.1	6	28.6	28.6	M6	SA202	0.30
SAPF 203	17	81	63.5	7	2	7.1	6	28.6	28.6	M6	SA 203	0.30
SAPF 204	20	90	71.5	8	2	9	7	31	33.3	M8	SA 204	0.33
SAPF 205	25	95	76	9	2	9	7.5	31	38.1	M8	SA 205	0.42
SAPF 206	30	113	90.5	9.5	2.6	11	8	35.7	44.5	M10	SA 206	0.65
SAPF 207	35	122	100	11	2.6	11	8.5	38.9	55.6	M10	SA 207	0.90

Références	Dimensions mm									Vis	Roult.	Poids kg
	d	a	e	M	t	s	n	B1				
SBPF 201	12	81	63.5	7	2	7.1	6	22		M6	SB 201	0.27
SBPF 202	15	81	63.5	7	2	7.1	6	22		M6	SB 202	0.27
SBPF 203	17	81	63.5	7	2	7.1	6	22		M6	SB 203	0.27
SBPF 204	20	90	71.5	8	2	9	7	25		M8	SB 204	0.33
SBPF 205	25	95	76	9	2	9	7.5	27		M8	SB 205	0.38
SBPF 206	30	113	90.5	9.5	2.6	11	8	30		M10	SB 206	0.62
SBPF 207	35	122	100	11	2.6	11	8.5	32		M10	SB 207	0.82

Composition: Corps de palier en tôle, Roulement: Acier 100 Cr6 . Température de fonctionnement: - 20°C + 120°C

Nous consulter si : Autres dimensions ou si un autre roulement utilisé (SA, SB ou UK)