



Roulements acier

Page 1 / 2



Roulements: Ouvert ()



Protégé (ZZ)



Etanche (2RS)

Références	Dimensions en mm			Charges				Vitesse maxi		Poids en g	
	Ø d	Ø D	h	dyn. C	kN	stat. C	kN	Graisse tr / mn	Huile tr / mn		
6000	10	28	8	4.55	1.95	28000	17000	28000	34000	20	
6000 2RS											-
6000 ZZ											-
6200	10	30	9	5.10	2.40	26000	17000	26000	38000	32	
6200 2RS											-
6200 ZZ											-
6300	10	35	11	8.10	3.45	20000	14000	20000	26000	57	
6300 2RS											-
6300 ZZ											-
6001	12	28	8	5.11	2.41	26000	17000	26000	32000	22	
6001 2RS											-
6001 ZZ											-
6201	12	32	10	6.80	3.05	22000	15000	22000	28000	37	
6201 2RS											-
6201 ZZ											-
6301	12	37	12	9.65	4.15	19000	12000	19000	24000	65	
6301 2RS											-
6301 ZZ											-
6002	15	32	9	5.60	2.85	22000	14000	22000	28000	31	
6002 2RS											-
6002 ZZ											-
6202	15	35	11	7.65	3.75	19000	13000	19000	24000	46	
6202 2RS											-
6202 ZZ											-
6302	15	42	13	11.40	5.45	17000	11000	17000	20000	92	
6302 2RS											-
6302 ZZ											-
6003	17	35	10	6.00	3.25	20000	12000	20000	26000	42	
6003 2RS											-
6003 ZZ											-
6203	17	40	12	9.55	4.80	17000	11000	17000	20000	70	
6203 2RS											-
6203 ZZ											-
6303	17	47	14	13.40	6.55	16000	11000	16000	19000	120	
6303 2RS											-
6303 ZZ											-
6004	20	42	12	9.40	5.05	17000	11000	17000	20000	70	
6004 2RS											-
6004 ZZ											-
6204	20	47	14	12.80	6.65	15000	10000	15000	18000	118	
6204 2RS											-
6204 ZZ											-
6304	20	52	15	15.90	7.90	13000	8000	13000	16000	158	
6304 2RS											-
6304 ZZ											-
6005	25	47	12	10.10	5.85	15000	9500	15000	18000	86	
6005 2RS											-
6005 ZZ											-
6205	25	52	15	14.00	7.85	12000	8000	12000	15000	142	
6205 2RS											-
6205 ZZ											-
6305	25	62	17	20.60	11.30	11000	7500	11000	14000	250	
6305 2RS											-
6305 ZZ											-