

Roulement Ouvert ()



Roulement protégé



Roulement étanche (2rs)



Références			Ø d mm	Ø D mm	h mm	Charges kN		Vitesse max. t/mn			Poids g
Ouvert	Protégé	Étanche				Dyn C	Stat Co	Rlt. ouvert	Rlt. zz	Rlt. 2rs	
S 6811	* S 6811 zz	S 6811 2rs		72	9	6.64	6.52	10 800	9 180	6 480	85
S 6911	* S 6912 zz	S 6911 2rs		80	13	12.15	10.35	9 900	8 415	5 940	200
S 6011	S 6011 zz	S 6011 2rs	55	90	18	21.23	15.90	9 000	7 700	4 500	390
S 6211	S 6211 zz	S 6211 2rs		100	21	32.63	21.90	7 600	6 400	4 300	610
S 6311	S 6311 zz	S 6311 2rs		120	29	53.63	33.75	6 800	5 800	3 900	1 350
S 6812	* S 6812 zz	S 6812 2rs		78	10	8.77	8.40	9 900	8 415	5 940	115
S 6912	* S 6912 zz	S 6912 2rs		85	13	12.15	10.57	9 000	7 650	5 400	220
S 6012	S 6012 zz	S 6012 2rs	60	95	18	22.13	17.40	8 300	7 000	4 100	420
S 6212	S 6212 zz	S 6212 2rs		110	22	39.38	27.00	7 000	6 000	3 800	780
S 6312	S 6312 zz	S 6312 2rs		130	31	61.50	39.00	6 300	5 400	3 600	1700
S 6813	* S 6813 zz	S 6813 2rs		85	10	9.14	9.37	9 000	7 650	5 400	140
S 6913	* S 6913 zz	* S 6913 2rs		90	13	12.82	11.77	8 550	7 268	5 130	270
S 6013	S 6013 zz	S 6013 2rs	65	100	18	22.88	18.90	7 700	6 500	3 900	440
S 6213	S 6213 zz	S 6213 2rs		120	23	43.13	30.00	6 500	5 500	3 600	990
S 6313	S 6313 zz	S 6313 2rs		140	33	69.38	45.00	5800	4 900	3 300	2 100
S 6814	* S 6814 zz	S 6814 2rs		90	10	9.16	9.75	8 100	6 885	4 860	150
S 6914	* S 6914 zz	* S 6914 2rs		100	16	17.55	15.60	7 650	6 503	4 590	370
S 6014	S 6014 zz	S 6014 2rs	70	110	20	28.50	23.25	7 100	6 100	3 600	600
S 6214	S 6214 zz	S 6214 2rs		125	24	46.50	33.00	6 000	5 100	3 400	1 050
S 6314	-	S 6314 2rs		150	35	78.00	51.00	5 400	-	3 100	2 500
S 6815	* S 6815 zz	S 6815 2rs		95	10	9.37	10.57	7 650	6 503	4 590	160
S 6915	* S 6915 zz	* S 6915 2rs		105	16	17.85	14.25	7 200	6 120	4 320	380
S 6015	S 6015 zz	S 6015 2rs	75	115	21	29.53	25.13	6 700	5 700	3 300	640
S 6215	S 6215 zz	S 6215 2rs		130	25	49.50	37.13	5 600	4 800	3 200	1 200
S 6816	* S 6816 zz	S 6816 2rs		100	10	9.68	11.10	7 200	6 120	4 320	180
S 6916	* S 6916 zz	* S 6916 2rs	80	110	16	18.45	15.00	6 750	5 738	4 050	420
S 6016	S 6016 zz	S 6016 2rs		125	22	35.70	29.85	6 300	5 300	5 300	850
S 6216	S 6216 zz	S 6216 2rs		140	26	54.52	39.75	5 300	4500	4 500	1.400
S 6017	S 6017 zz	S 6017 2rs	85	130	22	34.87	32.32	6 000	5 000	5000	890
S 6217	-	S 6217 2rs		150	28	63.00	46.25	5 000	-	4 300	1.800
S 6018	-	S 6018 2rs	90	140	24	43.65	37.27	5 300	-	4 500	1.160
S 6218	-	S 6218 2rs		160	30	72.00	53.62	4 500	-	3 800	2.160
S 6019	-	S 6019 2rs	95	145	24	45.37	40.20	5 000	-	4 300	1.200
S 6020	-	S 6020 2rs	100	150	24	45.37	40.50	5 000	-	4 300	1.250

Pour toutes les autres séries, dimensions ou matières, veuillez nous consulter.

* références : Sur demande, exemple * S 6916 zz

